

Declaration of Performance

1. Product type: **PVCu Double Glazed PVCu Sash Window**
2. Product type number: **Casement Sash Window Type A+10 Rated**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351–1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210) ⁴	A2	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208) ⁴	3A	
9.3	Dangerous substances (EN 14351) ¹	NONE	
9.4	Load-bearing capacity of safety Device 2	350 N PASS	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance 3	<1.4W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability (EN 12207) ⁴	4	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems. **2** Report R12269 issued by Wintech 2223

3 BSI Notified Body No. 0086 Thermal Transmittance Report No. 7985266. **4** Report 1737 issued by ERA.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven* Dated.....16/12/16...



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD

Declaration of Performance

10. Product type: **PVCu Double Glazed PVCu Sash Window**
11. Product type number: **Casement Flush Sash Window Type A+10 Rated**
12. Intended use: **Not on escape route**
13. Manufacturer: **Kitson Trade Windows Ltd**
14. Authorised representative: **General Manager**
15. System of assessment of performance: **System 3**
16. Reference harmonised standard: **BS EN 14351–1:2006 + A1:2010**
17. European Technical Assessment: **Not applicable**
18. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances (EN 14351) ¹	NONE	
9.4	Load-bearing capacity of safety Device 2	350 N PASS	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance 3	<1.4W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability(EN 12207 BS6375-1:2015) ⁴	NPD	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems. **2** Report R12269 issued by Wintech 2223

3 BSI Notified Body No. 0086 Thermal Transmittance Report No. 7985266. **4** Report WIL 358552 issued by Exova.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager).....*P Garven*.....Dated.....16/12/16...



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD

Declaration of Performance

19. Product type: **PVCu Triple Glazed PVCu Sash Window**
20. Product type number: **Casement Sash Window Type A++21 Rated**
21. Intended use: **Not on escape route**
22. Manufacturer: **Kitson Trade Windows Ltd**
23. Authorised representative: **General Manager**
24. System of assessment of performance: **System 3**
25. Reference harmonised standard: **BS EN 14351–1:2006 + A1:2010**
26. European Technical Assessment: **Not applicable**
27. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210) ⁴	A2	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208) ⁴	3A	
9.3	Dangerous substances (EN 14351) ¹	NONE	
9.4	Load-bearing capacity of safety Device 2	350 N PASS	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance 3	<1.0W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability (EN 12207) ⁴	4	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems. **2** Report R12269 issued by Wintech 2223

3 BSI Notified Body No. 0086 Thermal Transmittance Report No. 7985266. **4** Report 1737 issued by ERA.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*Dated.....16/12/16...



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD

Declaration of Performance

- | | |
|---|---|
| 1. Product type: | PVCu Double Glazed Sash Window |
| 2. Product type number: | Tilt & Turn Window Type A6 Rated |
| 3. Intended use: | Not on escape route |
| 4. Manufacturer: | Kitson Trade Windows Ltd |
| 5. Authorised representative: | General Manager |
| 6. System of assessment of performance: | System 3 |
| 7. Reference harmonised standard: | BS EN 14351-1:2006 + A1:2010 |
| 8. European Technical Assessment: | Not applicable |
| 9. Declared performance: | |

	Essential Characteristic	Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances (EN 14351) ¹	NONE	
9.4	Load-bearing capacity of safety device	350 N PASS	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance ³	<1.4W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability (EN 12207) ⁴	0.61 (m3/h.m2)	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

¹ Statement issued by British Plastics Federation and Epwin Window Systems. ² Report R12269 issued by Wintech 2223

³ BSI Notified Body No. 0086 Thermal Transmittance Report No. 7985266. ⁴ Report No.R15810 issued by Wintech

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven* Dated.....16/12/16.....



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD

Declaration of Performance

- | | |
|---|---|
| 1. Product type: | PVCu Double Glazed Sash Window |
| 2. Product type number: | Casement Sash Window Type C Rated 1920 |
| 3. Intended use: | Not on escape route |
| 4. Manufacturer: | Kitson Trade Windows Ltd |
| 5. Authorised representative: | General Manager |
| 6. System of assessment of performance: | System 3 |
| 7. Reference harmonised standard: | BS EN 14351-1:2006 + A1:2010 |
| 8. European Technical Assessment: | Not applicable |
| 9. Declared performance: | |

	Essential Characteristic	Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety Device 2	350 N PASS	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance 3	<1.6W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability (EN 12207) 4	0	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems. **2** Report R12269 issued by Wintech 2223

3 BSI Notified Body No. 0086 Thermal Transmittance Report No. 7985266. **4** Report R2819 issued by Wintech.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven* Dated.....23/7/13.....



Kitson Trade Windows Limited
Alnwick, Northumberland NE66 2PD

Declaration of Performance

1. Product type: **PVCu Double Glazed Mixed Sash Window / Door**
2. Product type number: **WD007**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351-1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety device	N/A	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance (EN ISO 10077-1)	<1.7W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability	NPD	
9.9	Impact resistance	NPD	
9.10	Height	NPD	
9.11	Ability to release	NONE FITTED	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*.....Dated.....23/7/13.....



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD

Declaration of Performance

1. Product type: **PVCu Double Glazed Single Residential Door**
2. Product type number: **WD001**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351-1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety device	N/A	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance (EN ISO 10077-1)	<1.6W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability	NPD	
9.9	Impact resistance	NPD	
9.10	Height	NPD	
9.11	Ability to release	NONE FITTED	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*..... Dated.....23/7/13.....



Kitson Trade Windows Limited
Alnwick, Northumberland NE66 2PD

Declaration of Performance

1. Product type: **PVCu Double Glazed Double (French) Door**
2. Product type number: **WD002**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351-1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety device	N/A	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance (EN ISO 10077-1)	<1.7W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability	NPD	
9.9	Impact resistance	NPD	
9.10	Height	NPD	
9.11	Ability to release	NONE FITTED	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*..... Dated.....23/7/13.....



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD

Declaration of Performance

1. Product type: **PVCu Double Glazed/Solid Composite Door**
2. Product type number: **WD003**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351–1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety device	N/A	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance (EN ISO 10077-1)	<1.6W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability	NPD	
9.9	Impact resistance	NPD	
9.10	Height	NPD	
9.11	Ability to release	NONE FITTED	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*.....Dated.....23/7/13.....



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD

Declaration of Performance

1. Product type: **PVCu Double Glazed Tilt & Slide Patio Door**
2. Product type number: **WD004**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351-1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety device	N/A	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance (EN ISO 10077-1)	<1.7W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability	NPD	
9.9	Impact resistance	NPD	
9.10	Height	NPD	
9.11	Ability to release	NONE FITTED	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*..... Dated.....23/7/13.....



Kitson Trade Windows Limited
Alnwick, Northumberland NE66 2PD

Declaration of Performance

1. Product type: **PVCu Double Glazed In Line Patio Door**
2. Product type number: **WD005**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351–1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety device	N/A	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance (EN ISO 10077-1)	<1.7W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability	NPD	
9.9	Impact resistance	NPD	
9.10	Height	NPD	
9.11	Ability to release	NONE FITTED	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*.....Dated.....23/7/13.....



Kitson Trade Windows Limited
Alnwick, Northumberland NE66 2PD

Declaration of Performance

1. Product type: **PVCu Double Glazed Fold and Slide Door**
2. Product type number: **WD006**
3. Intended use: **Not on escape route**
4. Manufacturer: **Kitson Trade Windows Ltd**
5. Authorised representative: **General Manager**
6. System of assessment of performance: **System 3**
7. Reference harmonised standard: **BS EN 14351-1:2006 + A1:2010**
8. European Technical Assessment: **Not applicable**
9. Declared performance:

Essential Characteristic		Performance	Harmonised Technical Specification
9.1	Resistance to wind load (EN 12210)	NPD	BS EN 14351-1:2006 + A1:2010
9.2	Watertightness (EN 12208)	NPD	
9.3	Dangerous substances 1	NONE	
9.4	Load-bearing capacity of safety device	N/A	
9.5	Acoustic performance (EN ISO 140-3)	NPD	
9.6	Thermal transmittance (EN ISO 10077-1)	<1.7W/(m2.K)	
9.7	Radiation properties	NPD	
9.8	Air permeability	NPD	
9.9	Impact resistance	NPD	
9.10	Height	NPD	
9.11	Ability to release	NONE FITTED	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

1 Statement issued by British Plastics Federation and Epwin Window Systems.

Signed for and on behalf of Kitson Trade Windows Ltd. by:

Peter Garven (General Manager)..... *P Garven*..... Dated.....23/7/13.....



Kitson Trade Windows Limited

Alnwick, Northumberland NE66 2PD